

Determination of Yellow Change and Red Clearance Intervals

Yellow Change Interval

$$\text{Yellow interval} = t + \frac{v}{2a + 64.4g}$$

t = perception reaction time, typically 1.5 seconds
 v = design speed*, in ft/sec
 a = deceleration rate, typically 11.2 ft/sec²
 g = grade

Round up to nearest 0.1 second.

Minimum yellow change interval is 3.0 seconds.

Hold stakeholder discussion** when calculated yellow change interval is longer than 6.0 seconds.

Red Clearance Interval

$$\text{Red interval} = \frac{w}{v} \quad \begin{array}{l} w = \text{width of intersection, in feet} \\ v = \text{design speed*, in ft/sec} \end{array}$$

If the initial calculation results in an all red time longer than 3.0 seconds, recalculate the red time as follows:

$$\text{Recalculated red interval} = \frac{1}{2} \left(\frac{w}{v} - 3 \right) + 3$$

Round up to nearest 0.1 second.

Red clearance interval should be between 1.0 and 6.0 sec.

Hold stakeholder discussion** when recalculated red clearance interval is longer than 4.0 seconds.

Notes

*Design speed is the speed limit unless a speed study determines that the 85th percentile speed is faster or intersection geometrics compel vehicles to traverse the intersection slower.

**The purpose of a stakeholder discussion is to provide advance notification and involvement to stakeholders and provide an opportunity to consider possible countermeasures.

For most left turn lanes, assume a speed of 20 mph (32 kph) to 30 mph (48 kph). For locations with unusual conditions a higher or lower speed may be appropriate.

For separate left turn phases, calculate yellow and red intervals.

For left turns without a separate phase, calculate yellow and red times for both the through movement and the left turn movement. Use the highest yellow and enough red to equal the highest total time.

Where existing times are higher than calculated times, use the calculated values unless there is a documented history of the need for higher times. If approach is high speed and existing times are significantly higher than the calculated times, use the calculated values but consider adding a note to the plan to direct field forces to reduce the time incrementally. Include in the note how much and how often to reduce time until the final value is reached. (Ex. Existing Yellow Change Interval for phase 2 may be decreased by 0.2 seconds per week until the required value is reached.)

Where revising a location or adding a new signal along a corridor, consider comparing clearance times at adjacent intersections to new calculations to meet driver expectations.

Sources:
Traffic Engineering Handbook, Fifth Edition, Institute of Transportation Engineers, 1999.

A Policy on Geometric Design of Highways and Streets, Fourth Edition, American Association of State Highway and Transportation Officials, 2001.

Change and Clearance Intervals

SIGNAL DESIGN SECTION
 TRANSPORTATION MOBILITY AND SAFETY DIVISION
 NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

12-10

STD. NO.

5.2.2

SHEET 4 OF 4